

Air quality monitoring

Thermo Scientific Model 42i NO-NO₂-NO_x Chemiluminescent Gas Analyzer

Model 42i NO-NO₂-NO_x Analyzer

The Thermo Scientific™ Model 42i NO-NO₂-NO_x Analyzer utilizes chemiluminescence technology to measure the amount of nitrogen oxides in the air from sub-ppb levels up to 100 ppm.

Introduction

The Model 42i Analyzer is a single chamber, single photomultiplier tube design that cycles between the NO and NO_x modes.

The 42i Analyzer has independent outputs for NO, NO₂ and NO_x and each can be calibrated separately. Dual range and auto range are standard features as well. If required, the instrument can be operated continuously in either the NO or NO_x modes allowing for response times of less than five seconds. Temperature and pressure correction are standard features. User settable alarm levels for concentration and a wide variety of internal diagnostics are available from an easy-to-follow menu structure.

This state-of-the-art gas analyzer offers features such as an Ethernet port as well as flash memory for increased data storage.

Ethernet connectivity provides efficient remote access, allowing the user to download measurement information directly from the instrument without having to be onsite.

Easily programmable shortcut keys allow you to jump directly to frequently accessed functions, menus or screens. The larger interface screen can display up to five lines of measurement information while the primary screen remains visible.

Features

- Ethernet connectivity for efficient remote access
- Enhanced user interface with one button programming and large display screen
- Flash memory for increased data storage and user downloadable software
- Enhanced electronics design optimizes product commonality

Thermo Scientific Model 42i NO-NO₂-NO_x Analyzer

Specifications	
Preset ranges	0–0.05, 0.1, 0.2, 0.5, 1, 2, 5, 10, 20, 50 and 100 ppm; 0–0.1, 0.2, 0.5, 1, 2, 5, 10, 20, 50, 100 and 150 mg/m ³
Custom ranges	0–0.05 to 100 ppm; 0–0.1 to 150 mg/m ³
Zero noise	0.20 ppb RMS (60 second averaging time)
Lower detectable limit	0.40 ppb (60 second averaging time)
Zero drift (24 hour)	< 0.40 ppb
Span drift (24 hour)	+/- 1% full scale (24 hour)
Response time	40 seconds (10 second average time) 80 seconds (60 second average time) 300 seconds (300 second average time)
Precision	+/-0.4 ppb (500 ppb range)
Sample flow rate	0.6 liters/min.
Operating temperature	59°–95°F (15°– 35°C), safely operated 32°–113°F (0°–45°C)
Power requirements	100 VAC, 115 VAC, 220-240 VAC +/-10% @ 300W
Size and weight	16.75" (W) • 8.62" (H) • 23" (D), 55 lbs. (25 kg)
Outputs	Selectable voltage, RS232/RS485, TCP/IP, 10 status relays, and power fail indication (standard). 0–20 or 4–20 mA isolated current output (optional)
Inputs	16 digital inputs (standard), 8 0-10 Vdc analog inputs (optional)
Approvals and certifications	U.S. EPA reference method: RFNA-1289-074; MCerts certified: MC070093/00; EN14211: 936/21203248/C Report; NF certificate: 05/01; UKCA
Country of origin	India or China

To maintain optimal product performance, you need immediate access to experts worldwide, as well as priority status when your air quality equipment needs repair or replacement. We offer comprehensive, flexible support solutions for all phases of the product life cycle. Through predictable, fixed-cost pricing, our services help protect the return on investment and total cost of ownership of your Thermo Fisher Scientific products. For more information on our comprehensive service solutions, visit thermofisher.com/EPMSservice.

Your order code: **Model 42i NO-NO₂-NO_x Analyzer**


Ordering information

Model 42i NO-NO ₂ -NO _x Analyzer
Choose the following configurations options to customize your own Model 42i Analyzer
Voltage options
A = 120 VAC 50/60 Hz (standard)
B = 220 VAC 50/60 Hz
D = 220 VAC 50/60 Hz w/China power cord
J = 100 VAC 50/60 Hz
Internal zero/span
N = No zero/span assembly (standard)
Z = Internal zero/span assembly
P = Internal permeation oven with zero/span assembly
E = Internal permeation oven with external/span assembly
Converter options
M = Molybdenum (standard)
S = Stainless steel
Sample handling
S = Standard plumbing (standard)
A = Ammonia scrubber
L = Lag volume
C = Lag volume and ammonia scrubber
T = Standard plumbing with sample permeation dryer
V = Lag volume with sample permeation dryer
Ozone handling
D = Drierite scrubber (standard)
P = Permeation dryer
Optional I/O
A = None (standard)
C = 0–20, 4–20 mA current output, 6 channels, 0–10 V analog input, 8-channel
Mounting hardware
A = Bench mounting and ears/handles, EIA

Learn more at thermofisher.com/cleanair

thermo scientific